

# No.2 Paste

Water resisting admixture for concrete and masonry.



Integral water resisting admixture for concrete and masonry, above or below ground. Recommended for use where coloured mortar or integral floor colours are used

**FEATURES & BENEFITS:**

- Lines the pores in the matrix to prevent water passage through the mortar.
- Improves durability and workability.
- Suitable for after trades.
- Recommended for use where coloured mortar or integral floor colours are used.
- For maximum water resistance.
- Versatile for custom made mixes.
- Increase durability of mortar mix.

**APPLICATION INSTRUCTIONS:**

**Preparation**

All surfaces to be treated must be free of oil, grease or other contamination which may inhibit the bond of the render. Any loose concrete should be removed prior to the application of any mortar or render containing No.2 Paste.

**Mixing**

No.2 Paste is suitable for application straight out of the container without prior mixing.

**Application**

Add the No.2 Paste to the mix at the rate of one litre per 40kg of Portland cement. Add the No.2 Paste to the gauge water rather than directly to the mix wherever possible. Do not pre-mix with any admixture, always add any other admixtures separately to the mix.

**Curing**

Mortars and renders modified with No.2 Paste should be cured with either Curecon W or Curecon PW.

**CLEAN UP:**

Clean all equipment with water immediately after use.

**ESTIMATING:**

**Approximate Material Usage**

One to two litres per 40KG of Portland cement.

**PACKAGING:**

No.2 Paste is supplied in 20 Litre and 200 Litre sizes.

**STORAGE:**

No.2 Paste is a water based product which must be stored in the original unopened containers.

**PRECAUTIONS:**

Where temperatures are less than 5°C or greater than 35°C are encountered, contact our technical staff for specific advice. Any contact with eyes or skin should be washed off with soap and clean water. Do NOT use solvent. If swallowed seek immediate medical treatment. Protective gloves, goggles and clothing should be worn. Do not use lime in water resistant mixes containing No.2 Paste. Avoid excessive use of No.2 Paste in doses greater than those recommended.

**AVAILABILITY:**

No.2 Paste is available Australia wide through the RLA Polymers distributor network. Please contact our head office on 1800 242 931 to find out where your nearest stockist will be.

**TECHNICAL SUPPORT:**

RLA Polymers manufactures a comprehensive range of high quality, high performance construction products. In addition, RLA Polymers offers technical support and on-site advice to specifiers, end users and contractors. Please contact your RLA Polymers sales representative or RLA Head Office for this service.

PRODUCT DATA	
Specific Gravity @ 25°C	0.98 gm/ml
Ph	9.5-10.5