



## PLUMMA'S TYPE P GREEN SOLVENT CEMENT

Chemwatch Hazard Alert Code: 3

RLA Polymers Pty Ltd

Chemwatch: 5226-44

Version No: 2.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Issue Date: 03/10/2016

Print Date: 09/12/2016

S.GHS.AUS.EN

### SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

#### Product Identifier

|                               |                                       |
|-------------------------------|---------------------------------------|
| Product name                  | PLUMMA'S TYPE P GREEN SOLVENT CEMENT  |
| Synonyms                      | Not Available                         |
| Proper shipping name          | ADHESIVES containing flammable liquid |
| Other means of identification | Not Available                         |

#### Relevant identified uses of the substance or mixture and uses advised against

|                          |   |
|--------------------------|---|
| Relevant identified uses | Use according to manufacturer's directions.<br>Type P Solvent Cement for pressure joints in PVC-U Pipes and Fittings. |
|--------------------------|---|

#### Details of the supplier of the safety data sheet

|                         |  |
|-------------------------|--|
| Registered company name | RLA Polymers Pty Ltd                           |
| Address                 | 215 Colchester Road Kilsyth VIC 3137 Australia |
| Telephone               | +61 3 9728 1644                                |
| Fax                     | +61 3 9728 6009                                |
| Website                 | www.rlagroup.com.au                            |
| Email                   | sales@rlagroup.com.au                          |

#### Emergency telephone number

|                                   |  |
|-----------------------------------|--|
| Association / Organisation        | Not Available  |
| Emergency telephone numbers       | +61 3 9728 1644 (RLA Group Technical Manager) business hours |
| Other emergency telephone numbers | 132766 (Security Monitoring Service)                         |

### SECTION 2 HAZARDS IDENTIFICATION

#### Classification of the substance or mixture

|                    |  |
|--------------------|--|
| Poisons Schedule   | S5   |
| Classification [1] | Flammable Liquid Category 2, Acute Toxicity (Oral) Category 4, Acute Toxicity (Dermal) Category 4, Acute Toxicity (Inhalation) Category 4, Eye Irritation Category 2A, Reproductive Toxicity Category 1B, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation), Specific target organ toxicity - single exposure Category 3 (narcotic effects), Aspiration Hazard Category 1 |
| Legend:            | 1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI   |

#### Label elements

|                    |  |
|--------------------|--|
| GHS label elements |  |
|--------------------|--|

SIGNAL WORD **DANGER**

#### Hazard statement(s)

|      |   |
|------|---|
| H225 | Highly flammable liquid and vapour.       |
| H302 | Harmful if swallowed.                     |
| H312 | Harmful in contact with skin.             |
| H332 | Harmful if inhaled.                       |
| H319 | Causes serious eye irritation.            |
| H360 | May damage fertility or the unborn child. |

Continued...

## TYPE P GREEN SOLVENT CEMENT

|        |   |
|--------|---|
| H335   | May cause respiratory irritation.                     |
| H336   | May cause drowsiness or dizziness.                    |
| H304   | May be fatal if swallowed and enters airways.         |
| AUH019 | May form explosive peroxides                          |
| AUH066 | Repeated exposure may cause skin dryness and cracking |

### Precautionary statement(s) Prevention

|      |  |
|------|--|
| P201 | Obtain special instructions before use.                            |
| P210 | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. |
| P271 | Use only outdoors or in a well-ventilated area.                    |
| P281 | Use personal protective equipment as required.                     |

### Precautionary statement(s) Response

|           |   |
|-----------|---|
| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. |
| P308+P313 | IF exposed or concerned: Get medical advice/attention.              |
| P331      | Do NOT induce vomiting.   |
| P363      | Wash contaminated clothing before reuse.                            |

### Precautionary statement(s) Storage

|           |  |
|-----------|--|
| P403+P235 | Store in a well-ventilated place. Keep cool. |
| P405      | Store locked up.                             |

### Precautionary statement(s) Disposal

|      |   |
|------|---|
| P501 | Dispose of contents/container in accordance with local regulations. |
|------|---|

## SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

### Substances

See section below for composition of Mixtures

### Mixtures

| CAS No   | %[weight] | Name                                       |
|----------|-----------|--|
| 78-93-3  | 10-30     | <u>methyl ethyl ketone</u>                 |
| 108-94-1 | 10-30     | <u>cyclohexanone</u>                       |
| 109-99-9 | 10-30     | <u>tetrahydrofuran</u>                     |
| 872-50-4 | <5        | <u>N-methyl-2-pyrrolidone</u>              |
|          | balance   | Ingredients determined not to be hazardous |

## SECTION 4 FIRST AID MEASURES

### Description of first aid measures

|                     |  |
|---------------------|--|
| <b>Eye Contact</b>  | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>Wash out immediately with fresh running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>  |
| <b>Skin Contact</b> | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>Immediately remove all contaminated clothing, including footwear.</li> <li>Flush skin and hair with running water (and soap if available).</li> <li>Seek medical attention in event of irritation.</li> </ul>  |
| <b>Inhalation</b>   | <ul style="list-style-type: none"> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor, without delay.</li> </ul>   |
| <b>Ingestion</b>    | <ul style="list-style-type: none"> <li><b>If swallowed do NOT induce vomiting.</b></li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Seek medical advice.</li> <li>Avoid giving milk or oils.</li> <li>Avoid giving alcohol.</li> <li>If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.</li> </ul> |

### Indication of any immediate medical attention and special treatment needed

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered

## TYPE P GREEN SOLVENT CEMENT

necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

Treat symptomatically.

for simple ketones:

### BASIC TREATMENT

- ▶ Establish a patent airway with suction where necessary.
- ▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- ▶ Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- ▶ Monitor and treat, where necessary, for pulmonary oedema .
- ▶ Monitor and treat, where necessary, for shock.
- ▶ **DO NOT use emetics.** Where ingestion is suspected rinse mouth and give up to 200 ml water (5mL/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- ▶ Give activated charcoal.

### ADVANCED TREATMENT

- ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Consider intubation at first sign of upper airway obstruction resulting from oedema.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- ▶ Monitor and treat, where necessary, for arrhythmias.
- ▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- ▶ Drug therapy should be considered for pulmonary oedema.
- ▶ Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ▶ Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

### EMERGENCY DEPARTMENT

- ▶ Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- ▶ Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- ▶ Consult a toxicologist as necessary.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

## SECTION 5 FIREFIGHTING MEASURES

### Extinguishing media

- ▶ Alcohol stable foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

### Special hazards arising from the substrate or mixture

|                             |  |
|-----------------------------|--|
| <b>Fire Incompatibility</b> | ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|-----------------------------|--|

### Advice for firefighters

|                              |  |
|------------------------------|--|
| <b>Fire Fighting</b>         | Alert Fire Brigade and tell them location and nature of hazard.<br>May be violently or explosively reactive.<br>Wear breathing apparatus plus protective gloves in the event of a fire.<br>Prevent, by any means available, spillage from entering drains or water course.   |
| <b>Fire/Explosion Hazard</b> | '' '<br>Liquid and vapour are highly flammable.<br>Severe fire hazard when exposed to heat, flame and/or oxidisers.<br>Vapour may travel a considerable distance to source of ignition.<br>Heating may cause expansion or decomposition leading to violent rupture of containers.<br>Combustion products include:<br>carbon dioxide (CO2)<br>nitrogen oxides (NOx)<br>other pyrolysis products typical of burning organic material.<br><b>WARNING:</b> Long standing in contact with air and light may result in the formation of potentially explosive peroxides. |
| <b>HAZCHEM</b>               | •3YE   |

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

|                     |  |
|---------------------|--|
| <b>Minor Spills</b> | <ul style="list-style-type: none"> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> </ul> |
|---------------------|--|

## TYPE P GREEN SOLVENT CEMENT

### Major Spills

- ▶ Clear area of personnel and move upwind.
- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- ▶ May be violently or explosively reactive.
- ▶ Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

|                          |  |
|--------------------------|--|
| <b>Safe handling</b>     | <p>Containers, even those that have been emptied, may contain explosive vapours.<br/>Do NOT cut, drill, grind, weld or perform similar operations on or near containers.<br/>May form explosive peroxides on standing or following concentration by distillation.<br/>Review of stocks and testing for peroxide content by given tested procedures at 3-monthly intervals is recommended, together with safe disposal of peroxidic samples.</p> <p>[Peroxide-containing residues can often be rendered innocuous by pouring into an excess of sodium carbonate solution]</p> <p><b>DO NOT allow clothing wet with material to stay in contact with skin</b></p> <p>Avoid all personal contact, including inhalation.<br/>Wear protective clothing when risk of exposure occurs.<br/>Use in a well-ventilated area.<br/>Prevent concentration in hollows and sumps.</p> |
| <b>Other information</b> | <p>Store in original containers in approved flame-proof area.<br/>No smoking, naked lights, heat or ignition sources.<br/><b>DO NOT store in pits, depressions, basements or areas where vapours may be trapped.</b><br/>Keep containers securely sealed.</p>  |

### Conditions for safe storage, including any incompatibilities

|                                |   |
|--------------------------------|---|
| <b>Suitable container</b>      | <p>Packing as supplied by manufacturer.<br/>Plastic containers may only be used if approved for flammable liquid.<br/>Check that containers are clearly labelled and free from leaks.<br/>For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.<br/>For materials with a viscosity of at least 2680 cSt. (23 deg. C)<br/>For manufactured product having a viscosity of at least 250 cSt.</p> |
| <b>Storage incompatibility</b> | <p>Avoid strong acids, bases.<br/>Avoid reaction with oxidising agents</p>  |

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### Control parameters

#### OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

| Source                       | Ingredient             | Material name             | TWA                             | STEL                            | Peak          | Notes         |
|------------------------------|------------------------|---------------------------|---------------------------------|---------------------------------|---------------|---------------|
| Australia Exposure Standards | methyl ethyl ketone    | Methyl ethyl ketone (MEK) | 445 mg/m <sup>3</sup> / 150 ppm | 890 mg/m <sup>3</sup> / 300 ppm | Not Available | Not Available |
| Australia Exposure Standards | cyclohexanone          | Cyclohexanone             | 100 mg/m <sup>3</sup> / 25 ppm  | Not Available                   | Not Available | Sk            |
| Australia Exposure Standards | tetrahydrofuran        | Tetrahydrofuran           | 295 mg/m <sup>3</sup> / 100 ppm | Not Available                   | Not Available | Sk            |
| Australia Exposure Standards | N-methyl-2-pyrrolidone | 1-Methyl-2-pyrrolidone    | 103 mg/m <sup>3</sup> / 25 ppm  | 309 mg/m <sup>3</sup> / 75 ppm  | Not Available | Sk            |

#### EMERGENCY LIMITS


| Ingredient             | Material name                                     | TEEL-1        | TEEL-2        | TEEL-3        |
|------------------------|---|---------------|---------------|---------------|
| methyl ethyl ketone    | Butanone, 2-; (Methyl ethyl ketone; MEK)          | Not Available | Not Available | Not Available |
| cyclohexanone          | Cyclohexanone; (Ketoexamethylene)                 | 60 ppm        | 830 ppm       | 5000 ppm      |
| tetrahydrofuran        | Tetrahydrofuran                                   | Not Available | Not Available | Not Available |
| N-methyl-2-pyrrolidone | Methyl 2-pyrrolidinone, 1-; (N-Methylpyrrolidone) | 30 ppm        | 32 ppm        | 190 ppm       |

| Ingredient             | Original IDLH    | Revised IDLH     |
|------------------------|------------------|------------------|
| methyl ethyl ketone    | 3,000 ppm        | 3,000 [Unch] ppm |
| cyclohexanone          | 5,000 ppm        | 700 ppm          |
| tetrahydrofuran        | 20,000 [LEL] ppm | 2,000 [LEL] ppm  |
| N-methyl-2-pyrrolidone | Not Available    | Not Available    |

### Exposure controls

|   |  |
|---|--|
| <b>Appropriate engineering controls</b> | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:<br/>Process controls which involve changing the way a job activity or process is done to reduce the risk.<br/>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.</p> |
|---|--|

## TYPE P GREEN SOLVENT CEMENT

|                                |  |
|--------------------------------|--|
| <b>Personal protection</b>     |   |
| <b>Eye and face protection</b> | Safety glasses with side shields.<br>Chemical goggles.<br>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.  |
| <b>Skin protection</b>         | See Hand protection below  |
| <b>Hands/feet protection</b>   | Wear chemical protective gloves, e.g. PVC.<br>Wear safety footwear or safety gumboots, e.g. Rubber<br>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.<br>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.<br>Personal hygiene is a key element of effective hand care.  |
| <b>Body protection</b>         | See Other protection below   |
| <b>Other protection</b>        | Overalls.<br>PVC Apron.<br>PVC protective suit may be required if exposure severe.<br>Eyewash unit.<br><ul style="list-style-type: none"> <li>Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.</li> <li>For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).</li> <li>Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds.</li> </ul> |
| <b>Thermal hazards</b>         | Not Available  |

**Recommended material(s)****GLOVE SELECTION INDEX**

Glove selection is based on a modified presentation of the: "Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

TYPE P GREEN SOLVENT CEMENT

| Material          | CPI |
|-------------------|-----|
| PE/EVAL/PE        | A   |
| BUTYL             | C   |
| BUTYL/NEOPRENE    | C   |
| CPE               | C   |
| HYPALON           | C   |
| NATURAL RUBBER    | C   |
| NATURAL+NEOPRENE  | C   |
| NEOPRENE          | C   |
| NEOPRENE/NATURAL  | C   |
| NITRILE           | C   |
| NITRILE+PVC       | C   |
| PVA               | C   |
| PVC               | C   |
| SARANEX-23        | C   |
| TEFLON            | C   |
| VITON/CHLOROBUTYL | C   |
| VITON/NEOPRENE    | C   |

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

**Respiratory protection**

**Type AK Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)**

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 5 x ES                       | AK-AUS / Class 1     | -                    | AK-PAPR-AUS / Class 1  |
| up to 25 x ES                      | Air-line*            | AK-2                 | AK-PAPR-2              |
| up to 50 x ES                      | -                    | AK-3                 | -                      |
| 50+ x ES                           | -                    | Air-line**           | -                      |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

**Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.**

**SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES****Information on basic physical and chemical properties**

|                   |  |
|-------------------|--|
| <b>Appearance</b> | Green viscous highly flammable liquid with a characteristic odour of MEK; does not mix with water. |
|-------------------|--|

## TYPE P GREEN SOLVENT CEMENT

|   |                   |  |                |
|---|-------------------|--|----------------|
| <b>Physical state</b>                               | Liquid            | <b>Relative density (Water = 1)</b>            | Not Available  |
| <b>Odour</b>  | Not Available     | <b>Partition coefficient n-octanol / water</b> | Not Available  |
| <b>Odour threshold</b>                              | Not Available     | <b>Auto-ignition temperature (°C)</b>          | 321            |
| <b>pH (as supplied)</b>                             | Not Applicable    | <b>Decomposition temperature</b>               | Not Available  |
| <b>Melting point / freezing point (°C)</b>          | Not Available     | <b>Viscosity (cSt)</b>                         | Not Available  |
| <b>Initial boiling point and boiling range (°C)</b> | Not Available     | <b>Molecular weight (g/mol)</b>                | Not Applicable |
| <b>Flash point (°C)</b>                             | -16               | <b>Taste</b>                                   | Not Available  |
| <b>Evaporation rate</b>                             | Not Available     | <b>Explosive properties</b>                    | Not Available  |
| <b>Flammability</b>                                 | HIGHLY FLAMMABLE. | <b>Oxidising properties</b>                    | Not Available  |
| <b>Upper Explosive Limit (%)</b>                    | 2                 | <b>Surface Tension (dyn/cm or mN/m)</b>        | Not Available  |
| <b>Lower Explosive Limit (%)</b>                    | 11.8              | <b>Volatile Component (%vol)</b>               | Not Available  |
| <b>Vapour pressure (kPa)</b>                        | Not Available     | <b>Gas group</b>                               | Not Available  |
| <b>Solubility in water (g/L)</b>                    | Immiscible        | <b>pH as a solution (1%)</b>                   | Not Applicable |
| <b>Vapour density (Air = 1)</b>                     | Not Available     | <b>VOC g/L</b>                                 | Not Available  |

### SECTION 10 STABILITY AND REACTIVITY

|   |  |
|---|--|
| <b>Reactivity</b>                         | See section 7  |
| <b>Chemical stability</b>                 | Unstable in the presence of incompatible materials.<br>Product is considered stable.<br>Hazardous polymerisation will not occur. |
| <b>Possibility of hazardous reactions</b> | See section 7  |
| <b>Conditions to avoid</b>                | See section 7  |
| <b>Incompatible materials</b>             | See section 7  |
| <b>Hazardous decomposition products</b>   | See section 5  |

### SECTION 11 TOXICOLOGICAL INFORMATION

#### Information on toxicological effects

|                     |   |
|---------------------|---|
| <b>Inhaled</b>      | Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.<br>The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.<br>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.  |
| <b>Ingestion</b>    | Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.<br>Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)   |
| <b>Skin Contact</b> | Skin contact with the material may be harmful; systemic effects may result following absorption.<br>Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.<br>Open cuts, abraded or irritated skin should not be exposed to this material<br>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.<br>The material may cause severe inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.   |
| <b>Eye</b>          | There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain.   |
| <b>Chronic</b>      | Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.<br>Ample evidence exists, from results in experimentation, that developmental disorders are directly caused by human exposure to the material.<br>Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.<br>There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.<br>Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.<br>The teratogenic potential, subchronic and long term inhalation toxicity of N-methyl-2-pyrrolidone (NMP) has been studied in rats. No evidence of nephrotoxicity was seen.<br>No carcinogenic effects were observed. Very high doses are embryotoxic to rats and mice. Reproductive effects have been reported in animals.<br>Long term cyclohexanone exposure may cause liver and kidney changes. Clouding of the eye lens and cataract development may occur.<br>Limited information is available on the chronic (long-term) effects of methyl ethyl ketone in humans. Chronic inhalation studies in animals have reported slight neurological, liver, kidney, and respiratory effects. No information is available on the developmental, reproductive, or carcinogenic effects of methyl ethyl ketone in humans. Developmental effects, including decreased foetal weight and foetal malformations, have been reported in mice and rats exposed to methyl ethyl ketone via inhalation and ingestion.<br>Repeated exposure to tetrahydrofuran (THF) and related compounds has been associated with liver inflammation and fatty degeneration of the liver. Animal testing suggests that this group of compounds can cause liver damage, irritation of the skin and airway, metabolic imbalance, gynaecological disturbance, damage to the adrenal glands and may increase the rate of cancer.<br>Cyclic ethers can cause cancers, especially of the liver.<br>Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS] |

|                                    |                 |                   |
|------------------------------------|-----------------|-------------------|
| <b>TYPE P GREEN SOLVENT CEMENT</b> | <b>TOXICITY</b> | <b>IRRITATION</b> |
|------------------------------------|-----------------|-------------------|

## TYPE P GREEN SOLVENT CEMENT

|                        |  |                                    |
|------------------------|--|------------------------------------|
|                        | Not Available  | Not Available                      |
| methyl ethyl ketone    | <b>TOXICITY</b>                                      | <b>IRRITATION</b>                  |
|                        | Dermal (rabbit) LD50: >8100 mg/kg <sup>[1]</sup>     | Eye (human): 350 ppm -irritant     |
|                        | Inhalation (rat) LC50: 23.5 mg/L/8hr <sup>[2]</sup>  | Eye (rabbit): 80 mg - irritant     |
|                        | Inhalation (rat) LC50: 50.1 mg/L/8 hr <sup>[2]</sup> | Skin (rabbit): 402 mg/24 hr - mild |
|                        | Oral (rat) LD50: 3474.9 mg/kg <sup>[1]</sup>         | Skin (rabbit):13.78mg/24 hr open   |
| cyclohexanone          | <b>TOXICITY</b>                                      | <b>IRRITATION</b>                  |
|                        | Dermal (rabbit) LD50: 947.8 mg/kg <sup>[2]</sup>     | Eye (human): 75 ppm                |
|                        | Inhalation (rat) LC50: 8000 ppm/4hr <sup>[2]</sup>   | Eye (rabbit): 0.25 mg/24h SEVERE   |
|                        | Oral (rat) LD50: 1535 mg/kg <sup>[2]</sup>           | Eye (rabbit): 4.74 mg SEVERE       |
|                        |  | Skin (rabbit): 500 mg(open) mild   |
| tetrahydrofuran        | <b>TOXICITY</b>                                      | <b>IRRITATION</b>                  |
|                        | dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>        | Not Available                      |
|                        | Inhalation (rat) LC50: >14.7 mg/16 hr <sup>[1]</sup> |                                    |
|                        | Inhalation (rat) LC50: 2100 ppm/3hr <sup>[2]</sup>   |                                    |
|                        | Inhalation (rat) LC50: 21000 ppm/3hr <sup>[2]</sup>  |                                    |
|                        | Inhalation (rat) LC50: 72 mg/L/2hr <sup>[2]</sup>    |                                    |
|                        | Oral (rat) LD50: <891 mg/kg <sup>[1]</sup>           |                                    |
| N-methyl-2-pyrrolidone | <b>TOXICITY</b>                                      | <b>IRRITATION</b>                  |
|                        | dermal (rat) LD50: >5000 mg/kg <sup>[1]</sup>        | Eye (rabbit): 100 mg - moderate    |
|                        | Inhalation (rat) LC50: 8300 ppm/4hr <sup>[2]</sup>   |                                    |
|                        | Oral (rat) LD50: 3914 mg/kg <sup>[2]</sup>           |                                    |

**Legend:**



1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.\* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

|   |  |
|---|--|
| <b>METHYL ETHYL KETONE</b>  | Methyl ethyl ketone is considered to have a low order of toxicity; however methyl ethyl ketone is often used in combination with other solvents and the toxic effects of the mix may be greater than either solvent alone. Combinations of n-hexane with methyl ethyl ketone and also methyl n-butyl ketone with methyl ethyl ketone show increase in peripheral neuropathy, a progressive disorder of nerves of extremities. Combinations with chloroform also show increase in toxicity  |
| <b>CYCLOHEXANONE</b>  | Cyclohexanone irritates the eye and the skin. Signs of CNS depression and weight loss have been noted at higher doses. Other features of toxicity include mottling of the lungs and degenerative changes in the liver and kidney. It is not considered to cause cancers, but it may reversibly reduce fertility. The substance is classified by IARC as Group 3:<br><b>NOT</b> classifiable as to its carcinogenicity to humans.<br>Evidence of carcinogenicity may be inadequate or limited in animal testing.  |
| <b>TETRAHYDROFURAN</b>  | The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.<br>Oral (human) LDLo: 50 mg/kg* [CCINFO]* Nil reported   |
| <b>N-METHYL-2-PYRROLIDONE</b>   | for N-methyl-2-pyrrolidone (NMP):<br><b>Acute toxicity:</b> In rats, NMP is absorbed rapidly after inhalation, oral, and dermal administration, distributed throughout the organism, and eliminated mainly by hydroxylation to polar compounds, which are excreted via urine. About 80% of the administered dose is excreted as NMP and NMP metabolites within 24 h. A probably dose-dependent yellow coloration of the urine in rodents is observed. The major metabolite is 5-hydroxy-N-methyl-2-pyrrolidone.  |
| <b>METHYL ETHYL KETONE &amp; TETRAHYDROFURAN &amp; N-METHYL-2-PYRROLIDONE</b> | Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. |
| <b>METHYL ETHYL KETONE &amp; CYCLOHEXANONE</b>                                | The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.   |
| <b>CYCLOHEXANONE &amp; TETRAHYDROFURAN</b>                                    | The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.   |

|  |   |                                 |   |
|--|---|---------------------------------|---|
| <b>Acute Toxicity</b>                    | ✓ | <b>Carcinogenicity</b>          | ⊘ |
| <b>Skin Irritation/Corrosion</b>         | ⊘ | <b>Reproductivity</b>           | ✓ |
| <b>Serious Eye Damage/Irritation</b>     | ✓ | <b>STOT - Single Exposure</b>   | ✓ |
| <b>Respiratory or Skin sensitisation</b> | ⊘ | <b>STOT - Repeated Exposure</b> | ⊘ |
| <b>Mutagenicity</b>                      | ⊘ | <b>Aspiration Hazard</b>        | ✓ |

## TYPE P GREEN SOLVENT CEMENT

## Legend:

-  – Data required to make classification available  
 – Data Not Available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

## Toxicity

| Ingredient             | Endpoint | Test Duration (hr) | Species                       | Value       | Source |
|------------------------|----------|--------------------|-------------------------------|-------------|--------|
| methyl ethyl ketone    | LC50     | 96                 | Fish                          | 228.130mg/L | 3      |
| methyl ethyl ketone    | EC50     | 48                 | Crustacea                     | 308mg/L     | 2      |
| methyl ethyl ketone    | EC50     | 96                 | Algae or other aquatic plants | >500mg/L    | 4      |
| methyl ethyl ketone    | EC50     | 384                | Crustacea                     | 52.575mg/L  | 3      |
| methyl ethyl ketone    | NOEC     | 48                 | Crustacea                     | 68mg/L      | 2      |
| cyclohexanone          | LC50     | 96                 | Fish                          | 71.940mg/L  | 3      |
| cyclohexanone          | EC50     | 72                 | Algae or other aquatic plants | 32.9mg/L    | 5      |
| cyclohexanone          | EC10     | 72                 | Algae or other aquatic plants | 3.56mg/L    | 4      |
| cyclohexanone          | NOEC     | 24                 | Fish                          | ca.5mg/L    | 1      |
| tetrahydrofuran        | LC50     | 96                 | Fish                          | 72.742mg/L  | 3      |
| tetrahydrofuran        | EC50     | 96                 | Algae or other aquatic plants | 310.515mg/L | 3      |
| tetrahydrofuran        | EC50     | 384                | Crustacea                     | 17.029mg/L  | 3      |
| tetrahydrofuran        | NOEC     | 24                 | Fish                          | >=5mg/L     | 1      |
| N-methyl-2-pyrrolidone | LC50     | 96                 | Fish                          | 464mg/L     | 1      |
| N-methyl-2-pyrrolidone | EC50     | 48                 | Crustacea                     | ca.4897mg/L | 1      |
| N-methyl-2-pyrrolidone | EC50     | 72                 | Algae or other aquatic plants | >500mg/L    | 1      |
| N-methyl-2-pyrrolidone | EC50     | 384                | Crustacea                     | 133.481mg/L | 3      |
| N-methyl-2-pyrrolidone | NOEC     | 504                | Crustacea                     | 12.5mg/L    | 2      |

**Legend:** Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

**DO NOT** discharge into sewer or waterways.

## Persistence and degradability

| Ingredient             | Persistence: Water/Soil   | Persistence: Air             |
|------------------------|---------------------------|------------------------------|
| methyl ethyl ketone    | LOW (Half-life = 14 days) | LOW (Half-life = 26.75 days) |
| cyclohexanone          | LOW                       | LOW                          |
| tetrahydrofuran        | LOW                       | LOW                          |
| N-methyl-2-pyrrolidone | LOW                       | LOW                          |

## Bioaccumulative potential

| Ingredient             | Bioaccumulation     |
|------------------------|---------------------|
| methyl ethyl ketone    | LOW (LogKOW = 0.29) |
| cyclohexanone          | LOW (BCF = 2.45)    |
| tetrahydrofuran        | LOW (LogKOW = 0.46) |
| N-methyl-2-pyrrolidone | LOW (BCF = 0.16)    |

## Mobility in soil

| Ingredient             | Mobility             |
|------------------------|----------------------|
| methyl ethyl ketone    | MEDIUM (KOC = 3.827) |
| cyclohexanone          | LOW (KOC = 15.15)    |
| tetrahydrofuran        | LOW (KOC = 4.881)    |
| N-methyl-2-pyrrolidone | LOW (KOC = 20.94)    |

## SECTION 13 DISPOSAL CONSIDERATIONS

## Waste treatment methods

|                                     |   |
|-------------------------------------|---|
| <b>Product / Packaging disposal</b> | <ul style="list-style-type: none"> <li>▶ Containers may still present a chemical hazard/ danger when empty.</li> <li>▶ Return to supplier for reuse/ recycling if possible.</li> </ul> <p>Otherwise:</p> <ul style="list-style-type: none"> <li>▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.</li> </ul> |
|-------------------------------------|---|

Continued...



## TYPE P GREEN SOLVENT CEMENT

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:


- ▶ Reduction
- ▶ Reuse
- ▶ Recycling
- ▶ Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

- ▶ **DO NOT allow wash water from cleaning or process equipment to enter drains.**
- ▶ It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- ▶ Recycle wherever possible.
- ▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- ▶ Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).
- ▶ Decontaminate empty containers.

### SECTION 14 TRANSPORT INFORMATION

#### Labels Required

|                         |   |
|-------------------------|---|
|                         |  |
| <b>Marine Pollutant</b> | NO  |
| <b>HAZCHEM</b>          | •3YE  |

#### Land transport (ADG)

|                                     |                                       |                |
|-------------------------------------|---------------------------------------|----------------|
| <b>UN number</b>                    | 1133                                  |                |
| <b>UN proper shipping name</b>      | ADHESIVES containing flammable liquid |                |
| <b>Transport hazard class(es)</b>   | Class                                 | 3              |
|                                     | Subrisk                               | Not Applicable |
| <b>Packing group</b>                | II                                    |                |
| <b>Environmental hazard</b>         | Not Applicable                        |                |
| <b>Special precautions for user</b> | Special provisions                    | Not Applicable |
|                                     | Limited quantity                      | 5 L            |

#### Air transport (ICAO-IATA / DGR)

|                                     |   |                |
|-------------------------------------|---|----------------|
| <b>UN number</b>                    | 1133  |                |
| <b>UN proper shipping name</b>      | Adhesives containing flammable liquid                     |                |
| <b>Transport hazard class(es)</b>   | ICAO/IATA Class   | 3              |
|                                     | ICAO / IATA Subrisk                                       | Not Applicable |
|                                     | ERG Code  | 3L             |
| <b>Packing group</b>                | II  |                |
| <b>Environmental hazard</b>         | Not Applicable  |                |
| <b>Special precautions for user</b> | Special provisions  | A3             |
|                                     | Cargo Only Packing Instructions                           | 364            |
|                                     | Cargo Only Maximum Qty / Pack                             | 60 L           |
|                                     | Passenger and Cargo Packing Instructions                  | 353            |
|                                     | Passenger and Cargo Maximum Qty / Pack                    | 5 L            |
|                                     | Passenger and Cargo Limited Quantity Packing Instructions | Y341           |
|                                     | Passenger and Cargo Limited Maximum Qty / Pack            | 1 L            |

#### Sea transport (IMDG-Code / GGVSee)

|                                   |                                       |                |
|-----------------------------------|---------------------------------------|----------------|
| <b>UN number</b>                  | 1133                                  |                |
| <b>UN proper shipping name</b>    | ADHESIVES containing flammable liquid |                |
| <b>Transport hazard class(es)</b> | IMDG Class                            | 3              |
|                                   | IMDG Subrisk                          | Not Applicable |
| <b>Packing group</b>              | II                                    |                |
| <b>Environmental hazard</b>       | Not Applicable                        |                |

## TYPE P GREEN SOLVENT CEMENT

|                              |                    |                |
|------------------------------|--------------------|----------------|
| Special precautions for user | EMS Number         | F-E, S-D       |
|                              | Special provisions | Not Applicable |
|                              | Limited Quantities | 5 L            |

## Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

## SECTION 15 REGULATORY INFORMATION

## Safety, health and environmental regulations / legislation specific for the substance or mixture

## METHYL ETHYL KETONE(78-93-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards  
Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

## CYCLOHEXANONE(108-94-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards  
Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)  
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

## TETRAHYDROFURAN(109-99-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards  
Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

## N-METHYL-2-PYRROLIDONE(872-50-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards  
Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

| National Inventory            | Status   |
|-------------------------------|--|
| Australia - AICS              | Y  |
| Canada - DSL                  | Y  |
| Canada - NDSL                 | N (cyclohexanone; N-methyl-2-pyrrolidone; tetrahydrofuran; methyl ethyl ketone)  |
| China - IECSC                 | Y  |
| Europe - EINEC / ELINCS / NLP | Y  |
| Japan - ENCS                  | Y  |
| Korea - KECI                  | Y  |
| New Zealand - NZIoC           | Y  |
| Philippines - PICCS           | Y  |
| USA - TSCA                    | Y  |
| <b>Legend:</b>                | Y = All ingredients are on the inventory<br>N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) |

## SECTION 16 OTHER INFORMATION

## Other information

## Ingredients with multiple cas numbers

| Name                   | CAS No               |
|------------------------|----------------------|
| N-methyl-2-pyrrolidone | 872-50-4, 26138-58-9 |

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net](http://www.chemwatch.net)

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

## Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average PC –

STEL: Permissible Concentration-Short Term Exposure Limit IARC:

International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit.

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.