

Rendacure

High solids, PVA based curing compound for concrete

DESCRIPTION

Rendacure is a high solids, polymer emulsion specifically formulated for the curing of concrete where after trades are to be applied. The specially selected polymers contained in Rendacure produces a fast drying membrane without the problems of wax or solvent based coatings.

ADVANTAGES

- Excellent adhesion
- Dries clear
- Wax free
- Fast drying
- Easy application
- Water based for safe application

TYPICAL PROPERTIES

Drying Time @20°C 30 minutes

Note: Drying will be quicker in warm weather and on porous substrates.

APPLICATION INSTRUCTIONS

Preparation

Stir the contents of the drum before application. When using Rendacure as a dust sealer on old concrete ensure the surface is clean and free of oils and other contaminants.

Mixing

No mixing or dilution is necessary. Use the Rendacure as supplied to ensure optimum results.

Application

For optimum water retention in new concrete apply the Rendacure as soon as possible after the

disappearance of any surface water and final troweling. The green fugitive dye assists with obtaining an even coverage.

Apply the Rendacure to the substrate using a brush, roller or spray at 5 sq. m per litre. Avoid letting the membrane pool in any low spots on the floor. Areas which quickly absorb the membrane may require a second coat to adequately seal the substrate. On vertical surfaces apply the membrane as soon as the formwork is removed.

CLEAN UP

Clean all equipment with water immediately after use.

ESTIMATING

Packaging

Rendacure is supplied in 20 and 200 litre containers.

ESTIMATING DATA

A 20 litre drum of Rendacure will cover approximately 100 m² at an average application rate of 5 m² per litre. A broomed or brushed surface will reduce the area covered by the membrane.

STORAGE

Rendacure is a polymer emulsion based product which must stored in a dry area off the ground away from extremes of temperature.

PRECAUTIONS

Do not use Rendacure in areas subject to rising damp or in wet areas. Where temperatures less than 0°C or greater than 40°C are encountered, contact our Technical Staff for specific advice.

MARKETING SERVICES

THOMSON WHITE AUST P/L
250 Princes Hwy Dandenong Vic 3175
Tel: (03) 9791 8211
Fax: (03) 9791 8644
Email: ask@thomsonwhite.com.au

RENDACURE

NOTE

Material safety data sheets for these and all Aftek products are available on request. Read the MSDS and product label carefully before using.

All reasonable care is taken in the compilation of this data sheet. All recommendations regarding use are made without guarantee as the conditions of use are beyond the control of the manufacturer.

ALLIED PRODUCTS

Aftek manufactures a broad range of construction products including.

Grouts

Coatings

Admixtures

Adhesives

Sealants

Floor Toppings

Floor Levelling Compounds

Concrete Repair