

STRIPFORM

OIL BASED FORM RELEASE AGENT

DESCRIPTION

Stripform is an oil based form release agent specifically formulated for application to timber and steel formwork

ADVANTAGES

- Economical
- Easy Application
- Solvent Free
- Clean Release

TYPICAL PROPERTIES

Specific Gravity @ 20degC 0.95gm/ml

APPLICATION INSTRUCTIONS

Preparation

All formwork must be free of oil, grease or other contamination which may affect the concrete appearance.

Application

Stripform is suitable for use straight out of the drum without mixing. Apply the Stripform to the formwork using a brush, roller or spray at the rate of 8-10m² per litre. Avoid an excess of Stripform on the surface to prevent a dusty or stained finish on the concrete.

CURING

The application on Curecon WB as a curing membrane will reduce premature drying and shrinkage.

CLEANUP

Clean all equipment with water immediately after use. coat tools and forms with Stripform before storage to protect against corrosion.

ESTIMATING

Packaging

Stripform is supplied in 20 litre and 200 litre drums.

STORAGE

Stripform is an oil based product which must be stored in a dry area off the ground.

PRECAUTIONS

Where temperatures less than 5degC or greater than 35degC are encountered, contact our Technical Staff for specific advice.

This product is classified as non hazardous under Worksafe guidelines, but should still be handles with due care, Any contact with eyes or skin should be washed off with clean soapy water. Protective gloves and clothing should be worn.

NOTE

Safety data sheets for these and all AFTEK products are available on request. Read the SDS and product label carefully before using. All reasonable care is taken in the compilation of this data sheet. All recommendations regarding use are made without guarantee as the conditions of use are beyond the control of the manufacturer.

ALLIED PRODUCTS

Aftek manufactures a broad range of construction products including:

- Grouts
- Coatings
- Admixtures
- Adhesives
- Sealants
- Floor Toppings
- Floor Levelling Compounds
- Concrete Repair



Product:	STRIPFORM
Issue Date:	NOV 2017
Issue No:	DO2

The information and any recommendations relating to the application and end -use of all AFTEK products are provided in good faith based on AFTEK's knowledge and experience of the products. In applications, the differences in materials, and variances of substrates and actual site conditions can vary such that no warranty in respect of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be taken as inferred either from this information, or from any written recommendations, or from any other advice offered by AFTEK. The proprietary rights of third parties must be observed. All orders are accepted subject to our sale terms and conditions. All users should always refer to the most recent and up to date issue of the Technical Data Sheet for the product concerned, which is available on request. It is recommended that products should always be properly stored, handled and applied under tested and recommended conditions.