



RLA QuickSet Liquid Additive



DESCRIPTION:

RLA QuickSet is a Calcium Chloride based liquid additive designed to make any cement-based product set and develop initial strength quickly.

RECOMMENDED USE:

- RLA QuickSet is especially recommended for use with RLA cement-based adhesives.
- RLA QuickSet is recommended for use where a fastsetting result is required, such as doorways, stairs, access ramps and repair jobs, shopping centres etc.
- RLA QuickSet will accelerate the curing of any product based on Portland Cement.
- Quick Set is most effective in cold temperatures (5 to 15 degrees C).
- RLA QuickSet will work differently depending on the nature of the product, and the actual performance can only be established by trialling.
- RLA QuickSet can be used in cement-based tile adhesives, grouts, screed, render or any product based on Portland Cement.

SURFACE PREPARATION:

Ensure all mixing containers are clean, dry and free from excessive oil, dust, grease, wax, existing compounds, release agents, paint and any other loose contaminating materials.

APPLICATION:

Use Quick set to replace some of the gauging water in any Portland cement-based product.

For any 20Kg bag, use about 300mls as a moderate accelerator or 1 litre for a more aggressive result.

For example, for a bag of tile adhesive that typically uses 6L of water, mix up to 1 litre of Quick Set with 5L of water. For even more acceleration, try to use even less water, for example, 1L of Quick Set with 3.5L of water.

COVERAGE:

<u>Quickset</u>	<u>Water</u>	<u>Adhesive</u>	Set Time
0.3ml	5.7 Litres	20kg	24 HRS
1 Litre	5 Litres	20kg	3 HRS
1.5 Litre	4.5 Litres	20kg	2 HRS

PRECAUTIONS:

Do not use it in conjunction with metallic hardeners or reinforced concrete.

Quick Set will promote corrosion of steel.

Do not use at temperatures less than 5°C.

At regular and higher temperatures

Quick Set may significantly reduce the pot life and open time.

Quick Set may not be compatible with other additives. Always mix a trial batch first and check the characteristics. Quick Set is a strong eye irritant. Use eye protection and consult the SDS.

PACKAGING:

5-litre Containers

SHELF LIFE:

12 months in an unopened container stored above 5 °C and below 30°C



RLA Polymers Pty Ltd ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria, 3137 info@rlapolymers.com.au

T 1800 242 931



rlapolymers.com.au

Issue Date 01/08/2022



SAFETY & HANDLING:

- Wear suitable respiratory protection.
- Use in well-ventilated areas.
- Avoid breathing vapours
- Avoid contact with skin and eyes.
- Wear eye protection and suitable gloves and clothing.
- Do not eat, drink, or smoke while using this product.
- If on the skin, wash with plenty of soap and water,
- If in the eyes: rinse cautiously with water for several minutes.
- Remove contact lenses; if present, continue rinsing.
- If any skin or eye irritation persists or you feel unwell, get medical attention.

Safety Data Sheet is available upon request

FIRST AID:

If poisoning occurs, contact a doctor or Poisons Information Centre.

Skin: Wash off with warm water and soap.

If swallowed, DO NOT induce vomiting. Give a glass of

For advice or you feel unwell contact a Poisons Information Centre: Australia ph 131126,

New Zealand ph 0800 764 766 or a doctor at once.

If swallowed, do NOT induce vomiting. Immediately call the Poisons Information Centre or a doctor.

IF ON SKIN Remove immediately all contaminated clothing and wash skin with soap and water.

If skin irritation occurs, get medical advice/attention.

IF IN EYES Rinse carefully with water for several minutes. If eye irritation persists, get medical advice/attention.

WARRANTY STATEMENT:

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specifications.

We certify that this product is suitable for use when fully cured and will perform as described in our technical data sheet or other published materials.

RLA Polymers will replace the product free of charge when purchased from any legally verifiable source and where a product is proven to have been stored, handled, and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out per the relevant Australian Standard, the Floorcovering Manufacturer's instructions, and the floorcoverings must have been subject to normal traffic conditions.

Warranty doesn't apply if damage, loss, failure to follow instructions, or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to RLA Polymers.

The consumer is responsible for any expenses incurred in making a claim.

A claim form can be requested by:

1800 242 931 PHONE:

EMAIL: info@rlapolymers.com.au

MAIL: 215 Colchester Road Kilsyth Victoria 3137 (Attention Customer Service)

WEBSITE: www.rlapolymers.com.au

AUSTRALIAN CONSUMER LAW:

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality, and the failure does not amount to a major failure. The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

DISCLAIMER:

All statements and technical information contained herein are based on tests we believe to be reliable, but the accuracy thereof is not guaranteed.

Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.



RLA Polymers Pty Ltd ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria, 3137 info@rlapolymers.com.au T. 1800 242 931

