

RLA Vinyl Plank & Tile Adhesive



Features & Benefits:

- ✓ Installer Friendly
- ✓ High Shear Strength
- ✓ Green Star Compliant
- ✓ Solvent Free
- ✓ Low VOC Emission
- ✓ Anti-microbial Formulation
- ✓ Low Odour
- ✓ Australian Made

DESCRIPTION:

RLA Vinyl Plank Adhesive is a water-based acrylic emulsion with excellent plasticiser resistance and nonstaining properties.

It is protected against biodegradation, withstands everyday wet cleaning practices and is suitable for use over underfloor heating installations.

RECOMMENDED USE:

RLA Vinyl Plank Adhesive is a hard set adhesive suitable for bonding most PVC commercial and domestic vinyl sheeting products, vinyl composite tiles, PVC vinyl tiles and vinyl plank flooring.

It has a high initial grab and is ideal for bonding both supported and unsupported PVC vinyl. It may also be used to install hard-to-hold carpets and those with PVC backings.

COVERAGE:

- V1 1.6mm x 1.6mm notched trowel will achieve approximately 5 square metres per litre.
- V2 2.4mm x 2.4mm notched trowel will achieve up to 3 square metres per litre.

SURFACE PREPARATION:

To be by the current Australian Standard "Floor Coverings

- 1884-2021 Resilient Sheet & Tiles - Laying & Maintenance Practices"

All surfaces should be dry, smooth, sound, clean and free of wax, grease, oil, previously applied adhesive, and other contaminants.

Relative humidity of the concrete must be measured as per the AS1884- 2021 Australian Standard. RLA 265 may be applied onto concrete substrates with moisture content up to 85% relative humidity tested based on the In-Situ Probe method ASTM F2170 The alkalinity of the concrete (pH) must not be higher than 10. Subfloors must also be free of hydrostatic pressure.

Surface Preparation Continued:

And laitance on concrete substrates should be removed before using this adhesive.

Curing time is related to temperature; this product should not be applied at temperatures below 10°C. Test all concrete substrates for moisture content according to the current Australian Standards before priming or installing any floorcoverings. Priming is only generally required when installing on overly porous subfloors,

If priming is required, use [RLA PU95](#) or [RLA Universal Primer](#)

Indentations and uneven concrete subfloors should be treated with the Roberts and [RLA TruLevel](#) Product range of levelling compounds and by the manufacturer's recommendations.

APPLICATION:

For the application of Vinyl Planks and Tiles, it is recommended to apply the adhesive with a 1.6mm x1.6mm 'V1" notched trowel. Vinyl Planks with a textured or embossed backing; it is recommended to apply the adhesive with a 2.4mm x 2.4mm x 2.4mm 'V2" notched trowel.

Spread adhesive with the recommended notched trowel. Apply only the amount of adhesive that can be covered within the open time of the adhesive. Allow adhesive to develop some initial tack – generally 5-10 minutes at 20oC before lowering floorcovering into the WET Film of adhesive and rolling to ensure transfer has occurred. Tack-up time will depend upon atmospheric conditions and substrate absorbency. Complete installation according to vinyl manufacturer's instructions, ensuring the installation is rolled in both directions with the recommended roller weight before the adhesive setting.

Do not allow heavy traffic for 24 hours.

CLEAN UP:

Clean tools immediately after use with warm soapy water. The dried adhesive may be cleaned off using a suitable solvent cleaner applied to a damp cloth, then rubbed gently over the dried adhesive.

NOTES & PRECAUTIONS:

- Drying times can be extended when applied in cold ambient temperatures.
- Don't allow the adhesive to skin over or dry out; the floorcovering being bonded is essential to be installed into the Wet film of adhesive.
- Don't apply adhesive in direct sunlight.

INTERNAL USE ONLY.

SHELF LIFE / STORAGE:

12 months when stored in original unopened packaging
To be stored in a dry area off the ground.

CONTAINER SIZES:

15 litre Pail

SAFETY & HANDLING:

- Wear suitable respiratory protection.
- Use in well-ventilated areas.
- Avoid breathing vapours
- Avoid contact with skin and eyes.
- Wear eye protection and suitable gloves and clothing.
- Do not eat, drink, or smoke while using this product.
- If on the skin, wash with plenty of soap and water.
- If in the eyes: rinse cautiously with water for several minutes.
- Remove contact lenses; if present, continue rinsing.
- If any skin or eye irritation persists or you feel unwell, get medical attention.
- Safety Data Sheet is available upon request.

FIRST AID:

If poisoning occurs, contact a doctor or Poisons Information Centre.

WARRANTY STATEMENT:

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that this product is suitable for use when fully cured and will perform as described in our technical data sheet or other published materials.

RLA Polymers will replace the product free of charge when purchased from any legally verifiable source and where a product is proven to have been stored, handled, and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out per the relevant Australian Standard, the Floorcovering Manufacturer's instructions, and the floorcoverings must have been subject to normal traffic conditions.

Warranty doesn't apply if damage, loss, failure to follow instructions, or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to RLA

Polymers. The consumer is responsible for any expenses incurred in making a claim.

A claim form can be requested by:

PHONE: [1800 242 931](tel:1800242931)

EMAIL: info@rlapolymers.com.au

MAIL: [215 Colchester Road Kilsyth Victoria 3137 \(Attention Customer Service\)](mailto:215ColchesterRoadKilsythVictoria3137)

WEBSITE: www.rlapolymers.com.au

Skin: Wash off with warm water and soap.

If swallowed, DO NOT induce vomiting. Give a glass of water.

For advice or you feel unwell contact a Poisons Information

Centre: Australia ph 131126,

New Zealand ph 0800 764 766 or a doctor at once.

If swallowed, do NOT induce vomiting.

IF SWALLOWED, immediately call the Poisons Information Centre or a doctor.

IF ON SKIN Remove immediately all contaminated clothing and wash skin with soap and water.

If skin irritation occurs, get medical advice/attention.

IF IN EYES Rinse carefully with water for several minutes.

If eye irritation persists, get medical advice/attention.

AUSTRALIAN CONSUMER LAW:

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality, and the failure does not amount to a major failure. The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

DISCLAIMER:

All statements and technical information contained herein are based on tests we believe to be reliable, but the accuracy thereof is not guaranteed.

Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.