

RLA Roof & Gutter Trans RLA Polymers Pty Ltd

Version No: 2.1

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Issue Date: 18/05/2023 Print Date: 18/05/2023 S.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier	
Product name	RLA Roof & Gutter Trans
Chemical Name	Not Applicable
Synonyms	610324
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Paste used to seal gaps/ joints.

Use according to manufacturer's directions.

Details of the manufacturer or supplier of the safety data sheet

Registered company name	RLA Polymers Pty Ltd	
Address	215 Colchester Road, Kilsyth VIC 3137 Australia	
Telephone	+61 3 9728 1644, 1800 242 931	
Fax	+61 3 9728 6009	
Website	www.rlapolymers.com.au	
Email	sales@rlapolymers.com.au	

Emergency telephone number

Association / Organisation	RLA Polymers Pty Ltd	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone numbers	+61 3 9728 1644	+61 1800 951 288
Other emergency telephone numbers	1800 242 931	+61 3 9573 3188

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule Not Applicable Classification [1] Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 2A	

Label elements

Hazard pictogram(s)



Signal word

Hazard statement(s)

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

Version No: 2.1 Page 2 of 9 Issue Date: 18/05/2023 Print Date: 18/05/2023

RLA Roof & Gutter Trans

Precautionary statement(s) Prevention

P280	Wear protective gloves, protective clothing, eye protection and face protection.
P261	Avoid breathing mist/vapours/spray.
P264 Wash all exposed external body areas thoroughly after handling.	
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary statement(s) Response

P302+P352 IF ON SKIN: Wash with plenty of water and soap.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.	
P337+P313	If eye irritation persists: Get medical advice/attention.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
22984-54-9	1-3	methyltri(methylethylketoxime)silane
2224-33-1	0.3-1	vinyltris(methylethylketoxime)silane
1760-24-3	0.3-1	N-[3-(trimethoxysilyl)propyl]ethylenediamine
96-29-7	<1	methyl ethyl ketoxime
Legend: 1. Classification by vendor; 2. Classifi Classification drawn from C&L * EU I		assification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. EU IOELVs available

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	 If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
 Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

Fire Fighting

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- ▶ Wear breathing apparatus plus protective gloves in the event of a fire.

Version No: 2.1 Page 3 of 9 Issue Date: 18/05/2023 Print Date: 18/05/2023

RLA Roof & Gutter Trans

Fire/Explosion Hazard	 Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. The material is not readily combustible under normal conditions. However, it will break down under fire conditions and the organic component may burn. Not considered to be a significant fire risk. Heat may cause expansion or decomposition with violent rupture of containers. Decomposes on heating and produces: carbon dioxide (CO2) nitrogen oxides (NOx) silicon dioxide (SiO2) other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes.
HAZCHEM	Not Applicable

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety goggles. Trowel up/scrape up.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by all means available, spillage from entering drains or water courses.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling		
Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. 	
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. 	

Conditions for safe storage, including any incompatibilities

Suitable container	 Polyethylene or polypropylene container. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	Avoid strong acids, bases. Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

Linergency Linits			
Ingredient	TEEL-1	TEEL-2	TEEL-3
N-[3-(trimethoxysilyl)propyl]ethylenediamine	23 mg/m3	250 mg/m3	1,500 mg/m3
methyl ethyl ketoxime	30 ppm	56 ppm	250 ppm

Ingredient	Original IDLH	Revised IDLH
methyltri(methylethylketoxime)silane	Not Available	Not Available
vinyltris(methylethylketoxime)silane	Not Available	Not Available
N-[3-(trimethoxysilyl)propyl]ethylenediamine	Not Available	Not Available
methyl ethyl ketoxime	Not Available	Not Available

Occupational Exposure Banding

Page 4 of 9 Version No: 2.1 Issue Date: 18/05/2023 Print Date: 18/05/2023

RLA Roof & Gutter Trans

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit	
methyltri(methylethylketoxime)silane	D	> 0.1 to ≤ 1 ppm	
vinyltris(methylethylketoxime)silane	D	> 0.1 to ≤ 1 ppm	
N-[3-(trimethoxysilyl)propyl]ethylenediamine	D	> 0.1 to ≤ 1 ppm	
methyl ethyl ketoxime	D	> 0.1 to ≤ 1 ppm	
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.		

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Individual protection measures, such as personal protective equipment











Eye and face protection

- Safety glasses with side shields.
- Chemical goggles
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

Skin protection

See Hand protection below

- ► Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber

Hands/feet protection

NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

Body protection

See Other protection below

Other protection

- Overalls. P.V.C apron.
- Barrier cream.
- Skin cleansing cream

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	A-AUS / Class1 P2	-
up to 50	1000	-	A-AUS / Class 1 P2
up to 50	5000	Airline *	-
up to 100	5000	-	A-2 P2
up to 100	10000	-	A-3 P2
100+			Airline**

^{* -} Continuous Flow ** - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Translucent paste with oxime like odour; does not mix with water.		
Physical state	Non Slump Paste	Relative density (Water = 1)	1.03 @23C
Physical state	Non Siump Pasie	Relative defisity (water = 1)	1.03 @23C
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature (°C)	Not Available

Version No: 2.1 Page 5 of 9 Issue Date: 18/05/2023 Print Date: 18/05/2023

RLA Roof & Gutter Trans

Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	73 (CC) (Does not sustain combustion)	Taste	Not Available
Evaporation rate	<1 (BuAC = 1)	Explosive properties	Not Available
Flammability	Combustible.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Negligible	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	>1	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. The major toxic effects of MEKO, regardless of the route of administration, are anaemia with breakdown of red blood cells, rapid breathing and reversible reduction in spontaneous activity, motor coordination and muscle tone. At extremely high concentrations it may cause unconsciousness and failure of breathing.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	This material can cause eye irritation and damage in some persons.
Chronic	Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Methyl ethyl ketoxime causes an immediate but transient central nervous system depression, dose-related decreases in red blood cell counts accompanied by a compensatory marked increase in number of immature red cells, suggesting rapid red cell breakdown. Other effects include dose-related increase in spleen, liver and kidney weights. Deposits of iron have been reported in the liver and spleen at repeated high doses. This may increase risk of liver tumours.

	TOXICITY	IRRITATION
RLA Roof & Gutter Trans	Not Available	Not Available
	TOXICITY	IRRITATION
methyltri(methylethylketoxime)silane	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: adverse effect observed (irritating) ^[1]
	Oral (Rat) LD50: 2453 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
	TOXICITY	IRRITATION
vinyltris(methylethylketoxime)silane	dermal (rat) LD50: >2009 mg/kg ^[1]	Eye: adverse effect observed (irritating) ^[1]
	Oral (Rat) LD50: >2000 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Eye (rabbit): 15 mg SEVERE
I-[3-(trimethoxysilyl)propyl]ethylenediamine	Inhalation(Rat) LC50: >1.49<2.44 mg/l4h ^[1]	Eye: adverse effect observed (irreversible damage)[1]
	Oral (Rat) LD50: 1897 mg/kg ^[1]	Skin (rabbit): 500 mg mild
		Skin: no adverse effect observed (not irritating) ^[1]
	TOXICITY	IRRITATION
methyl ethyl ketoxime	Dermal (rabbit) LD50: >184<1840 mg/kg ^[1]	Eye (rabbit): 0.1 ml - SEVERE

Version No: 2.1 Page 6 of 9 Issue Date: 18/05/2023
Print Date: 18/05/2023

RLA Roof & Gutter Trans

Inhalation(Rat) LC50: >4.83 mg/l4h^[1]

Oral (Rat) LD50: >900 mg/kg^[1]

Legend:

 Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

VINYLTRIS(METHYLETHYLKETOXIME)SILANE No significant acute toxicological data identified in literature search. Allergic reactions involving the respiratory tract are usually due to interactions between IgE antibodies and allergens and occur rapidly. Allergic potential of the allergen and period of exposure often determine the severity of symptoms. Some people may be genetically more prone than others, and exposure to other irritants may aggravate symptoms. Allergy causing activity is due to interactions with proteins. Attention should be paid to atopic diathesis, characterised by increased susceptibility to nasal inflammation, asthma and eczema Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type; cell-mediated reactions (T lymphocytes) may be involved. Such allergy is of the delayed type with onset up to four hours following exposure. For N-[3-(trimethoxysilyI)propyI]-ethylenediamine (AEAPTMS) and its analogues: Animal testing shows that AEAPTMS is moderately irritating to (and can sensitise) the skin and severely irritating to the eyes. It also causes salivation and laboured breathing. There is no evidence that AEAPTMS causes genetic damage N-[3-(TRIMETHOXYSILYL)PROPYL]ETHYLENEDIAMINE or reproductive or developmental toxicity to date. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. Mammalian lymphocyte mutagen *Huls Canada ** Merck For methyl ethyl ketoxime (MEKO): At medium to high concentrations, MEKO increased the rate of liver tumours in METHYL ETHYL KETOXIME animal testing. This seems to be due to the breakdown of MEKO into a cancer-causing substance, and occurred more often in males. MEKO does not seem to cause mutations. Repeated exposure appeared to cause effects on the nose, spleen, liver, kidney and blood. METHYLTRI(METHYLETHYLKETOXIME)SILANE & The following information refers to contact allergens as a group and may not be specific to this product. VINYLTRIS(METHYLETHYLKETOXIME)SILANE & Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The N-[3-(TRIMETHOXYSILYL)PROPYL]ETHYLENEDIAMINE pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other & METHYL ETHYL KETOXIME allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. alpha,beta-Unsaturated oximes represent two previously unknown classes of prohaptens. Three putative metabolites were proposed as sensitising agents. These included two diastereometric alpha,beta-epoxy oximes and a nitro METHYLTRI(METHYLETHYLKETOXIME)SILANE & analogue. When tested in the LLNA, alpha, beta-epoxy oximes. VINYLTRIS(METHYLETHYLKETOXIME)SILANE Allergic Contact Dermatitis—Formation, Structural Requirements, and Reactivity of Skin Sensitizers. Ann-Therese Karlberg et al: Chem. Res. METHYLTRI(METHYLETHYLKETOXIME)SILANE & The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, VINYLTRIS(METHYLETHYLKETOXIME)SILANE & swelling, the production of vesicles, scaling and thickening of the skin. N-[3-(TRIMETHOXYSILYL)PROPYL]ETHYLENEDIAMINE

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	×
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

🗶 – Data either not available or does not fill the criteria for classification

Data available to make classification

SECTION 12 Ecological information

Toxicity

RLA Roof & Gutter Trans	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	72h	Algae or other aquatic plants	1mg/l	2
methyltri(methylethylketoxime)silane	EC50	72h	Algae or other aquatic plants	6.1mg/l	2
	LC50	96h	Fish	>100mg/l	2
	EC50	48h	Crustacea	201mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
vinyltris(methylethylketoxime)silane	NOEC(ECx)	72h	Algae or other aquatic plants	1mg/l	2
	EC50	72h	Algae or other aquatic plants	6.1mg/l	2

Version No: 2.1 Page 7 of 9 Issue Date: 18/05/2023 Print Date: 18/05/2023

RLA Roof & Gutter Trans

	LC50	96h	Fish	>100mg/l	2
	EC50	48h	Crustacea	201mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96h	Fish	597mg/l	2
	EC50	72h	Algae or other aquatic plants	5.5mg/l	2
N-[3-(trimethoxysilyl)propyl]ethylenediamine	EC50	96h	Algae or other aquatic plants	11mg/l	2
	EC50	48h	Crustacea	81mg/l	2
	NOEC(ECx)	72h	Fish	1.6mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
methyl ethyl ketoxime	BCF	1008h	Fish	0.5-0.6	7
	NOEC(ECx)	72h	Algae or other aquatic plants	~1.02mg/l	2
	EC50	72h	Algae or other aquatic plants	~6.09mg/l	2
	EC50	48h	Crustacea	~201mg/l	2
	LC50	96h	Fish	>100mg/l	2

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
methyltri(methylethylketoxime)silane	HIGH	HIGH
N-[3-(trimethoxysilyl)propyl]ethylenediamine	HIGH	HIGH
methyl ethyl ketoxime	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation	
methyltri(methylethylketoxime)silane	LOW (LogKOW = 7.8316)	
N-[3-(trimethoxysilyl)propyl]ethylenediamine	LOW (LogKOW = -1.6744)	
methyl ethyl ketoxime	LOW (BCF = 5.8)	

Mobility in soil

Ingredient	Mobility
methyltri(methylethylketoxime)silane	LOW (KOC = 590900)
N-[3-(trimethoxysilyl)propyl]ethylenediamine	LOW (KOC = 6856)
methyl ethyl ketoxime	LOW (KOC = 130.8)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- ► Consult State Land Waste Authority for disposal.
- ▶ Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO	
HAZCHEM	Not Applicable	

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group	
methyltri(methylethylketoxime)silane	Not Available	

Version No: 2.1 Page 8 of 9 Issue Date: 18/05/2023 Print Date: 18/05/2023

RLA Roof & Gutter Trans

Product name Group Not Available vinyltris(methylethylketoxime)silane N-[3-(trimethoxysilyl)propyl]ethylenediamine Not Available methyl ethyl ketoxime Not Available

Transport in bulk in accordance with the IGC Code

Product name	Ship Type
methyltri(methylethylketoxime)silane	Not Available
vinyltris(methylethylketoxime)silane	Not Available
N-[3-(trimethoxysilyl)propyl]ethylenediamine	Not Available
methyl ethyl ketoxime	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

methyltri(methylethylketoxime)silane is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

vinyltris(methylethylketoxime)silane is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

N-[3-(trimethoxysilyl)propyl]ethylenediamine is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

methyl ethyl ketoxime is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 6

Australian Inventory of Industrial Chemicals (AIIC) Chemical Footprint Project - Chemicals of High Concern List

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (methyltri(methylethylketoxime)silane; vinyltris(methylethylketoxime)silane; N-[3-(trimethoxysilyl)propyl]ethylenediamine; methyl ethyl ketoxime)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (methyltri(methylethylketoxime)silane; vinyltris(methylethylketoxime)silane; N-[3-(trimethoxysilyl)propyl]ethylenediamine)
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	18/05/2023
Initial Date	17/05/2023

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cance

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

Version No: 2.1 Page 9 of 9 Issue Date: 18/05/2023

RLA Roof & Gutter Trans

Print Date: 18/05/2023

ES: Exposure Standard OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China
EINECS: European INventory of Existing Commercial chemical Substances
ELINCS: European List of Notified Chemical Substances
NLP: No-Longer Polymers
ENCS: Existing and New Chemical Substances Inventory
KECI: Korea Existing Chemicals Inventory
NZIGC: Now Zeoland Inventory

NZIOC: New Zealand Inventory of Chemicals
PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory
FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances