

RENDACURE

HIGH SOLIDS, PVA BASED CONCRETE CURING COMPOUND



DESCRIPTION

RLA REDNACURE is a high solids, polymer emulsion specifically formulated for the curing of concrete where after trades are to be applied. The specially selected polymers contained in RENDACURE produces a fast drying membrane without the associated problems of wax or solvent based coatings.

FEATURES & BENEFITS

- Excellent adhesion
- Dries clear
- Wax free
- Fast drying
- Easy application
- Water based for safe application

USES

- As a curing compound over new concrete where after trades are to be applied
- Dust sealer for old concrete surfaces

APPLICATION

- Stir the contents of the drum before application
- No mixing or dilution is necessary - use Rendacure as supplied to ensure optimum results
- When using Rendacure as a dust sealer on old concrete, ensure the surface is clean and free of oils and other contaminants
- For optimum water retention in new concrete, apply the Rendacure as soon as possible after the disappearance of any surface water and final troweling
- The green fugitive dye assists with obtaining an even coverage
- Apply the Rendacure to the substrate using a brush roller or low pressure sprayer
- Avoid letting the membrane pool in any low spots on the floor
- Areas which quickly absorb the curing compound may require a second coat to adequately seal the substrate. On vertical surfaces apply the curing compound as soon as the formwork is removed.

COVERAGE

- Approximately 1litre per 5m²

NOTE: Coverage rates may vary subject to substrate porosity

DRY TIMES

- 30 minutes @ 20°C, 50% RH

NOTE: Drying times may vary subject to ambient/surface temperatures, humidity and substrate porosity

CLEAN UP

- Excess primer, tools and general equipment with water immediately after use while the product is still wet.

SHELF LIFE/STORAGE

- 12 months when stored in original unopened packaging
- Best stored in a dry area at room temperature
- Keep off cold floors and out of direct sunlight

CONTAINER SIZES

- 20litre containers

LIMITATIONS

- Do not apply RLA Rendacure A when surface or ambient temperatures are above 40°C or below 0°C Where temperatures less than 0°C or greater than 40°C are encountered, contact RLA Technical Department for specific advice
- Do not use Rendacure in areas subject to rising damp or in wet areas.

HEALTH & SAFETY

For information and advice on the safe handling, first aid, storage and disposal of chemical products, users must refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data

WARRANTY STATEMENT:

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that this product is suitable for use when fully cured and will perform as described in our technical data sheet or other published materials.

RLA Polymers will replace the product free of charge when purchased from any legally verifiable source and where a product is proven to have been stored, handled, and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out in accordance with relevant Australian Standards.

Warranty doesn't apply if damage, loss, failure to follow instructions, or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to RLA Polymers.

The consumer is responsible for any expenses incurred in making a claim.

A claim form can be requested by:

PHONE: 1800 242 931

EMAIL: info@rlapolymers.com.au

MAIL: 215 Colchester Road Kilsyth Victoria 3137
(Attention Customer Service)

WEBSITE: www.rlapolymers.com.au

AUSTRALIAN CONSUMER LAW:

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality, and the failure does not amount to a major failure. The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

DISCLAIMER:

All statements and technical information contained herein are based on tests we believe to be reliable, but the accuracy thereof is not guaranteed.

Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.

Version: 01

Issue date: 01/11/2023

RLA Polymers Pty Ltd ACN 004 709 915

Head Office
215 Colchester Road
Kilsyth, Victoria, 3137
Tel: 1800 242 931

New South Wales
363 Wentworth Ave
Pendle Hill, N.S.W, 2145

Queensland
57 Fulcrum Street
Richlands, QLD, 4077

South Australia
Unit 2/7 Berger Road
Wingfield, SA, 5013

Western Australia
24 Hanwell Way
Bassendean, W.A, 6054
Tel: 08 9279 8911