

# ECOSEAL

## GREEN TREATED PINE “CUT END” SEALER



### **DESCRIPTION:**

RLA ECOSEAL is a copper based, green coloured resealing solution for treated wood products intended for general outdoor applications such as landscaping, retaining walls, decking and fencing where cutting to length, notching, drilling, machining or other work may expose areas of un-penetrated wood.

### **USES**

- For resealing of treated timber products where cutting to length, rebating, notching, drilling or other work during installation or fitting exposes fresh timber surfaces
- Suitable for timber surfaces that are above ground as in H2 and H3 situations
- In-ground H4 as defined in AS1604.
- In H5 situations\*

\***Important:** cut end must not be placed in ground contact

### **APPLICATION:**

- Ensure adequate ventilation during use and avoid inhaling spray mist
- Shake can briefly before use
- The timber surfaces to be resealed should be dry and clean
- Turn spray tip so that the arrow on the nozzle points towards the surface to be sprayed
- Hold can 15 to 20 cm from the timber surface and apply the product liberally onto the freshly exposed surface until the solution ceases to absorb readily and just starts to run on the surface
- The product solution and the sprayed timber surface will initially be green but will fade to an olive green / brown in a few weeks
- Seek advice before over-painting

### **COVERAGE**

Coverage up to 2m<sup>2</sup> per can depending on wood condition and grain orientation (end grain will be most absorbent)

### **LIMITATIONS**

RLA ECOSEAL is only for supplementary use on treated wood products that have been preservative treated in accordance with AS1604.

This product is not suitable for application to, or protection of untreated timber

Do not use for any other purpose.

Use of this or an equivalent product is recommended in order to conform with manufacturers guarantees on treated wood products

### **SHELF LIFE/STORAGE**

- Store in a cool, secure place
- Protect from sunlight and do not expose to temperatures exceeding 50° C.
- Keep out of reach of children.
- Ecoseal is best used within 12 months from date of manufacture when stored in the above conditions in the original unopened container.

### **CONTAINER SIZES**

300g aerosol cans

### **WARNING**

- Intentional misuse by deliberately inhaling contents can be harmful or fatal
- Do not puncture the container even when empty
- Avoid breathing vapour and mist
- Provide adequate ventilation when spraying in confined spaces
- Avoid contact with eyes and skin

### **HEALTH AND SAFETY**

For information and advice on the safe handling, first aid, storage and disposal of chemical products, users must refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

PRODUCT INFORMATION:	
<b>Form</b>	White Spirits based solution in pressurised container
<b>Ingredients</b>	12 g/kg (20 g/L) copper (Cu) present as copper naphthenate. 1.3 g/kg (1g/L) permethrin 880 g/kg liquid hydrocarbons
<b>Propellant</b>	Hydrocarbon

**WARRANTY STATEMENT:**

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that this product is suitable for use when fully cured and will perform as described in our technical data sheet or other published materials.

RLA Polymers will replace the product free of charge when purchased from any legally verifiable source and where a product is proven to have been stored, handled, and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out in accordance with relevant Australian Standards.

Warranty doesn't apply if damage, loss, failure to follow instructions, or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to RLA Polymers.

The consumer is responsible for any expenses incurred in making a claim.

A claim form can be requested by:

**PHONE:** 1800 242 931

**EMAIL:** [info@rlapolymers.com.au](mailto:info@rlapolymers.com.au)

**MAIL:** 215 Colchester Road Kilsyth Victoria 3137  
(Attention Customer Service)

**WEBSITE:** [www.rlapolymers.com.au](http://www.rlapolymers.com.au)

**AUSTRALIAN CONSUMER LAW:**

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality, and the failure does not amount to a major failure. The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

**DISCLAIMER:**

All statements and technical information contained herein are based on tests we believe to be reliable, but the accuracy thereof is not guaranteed.

Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.

Version: 01

Issue date: 12/11/2023

**RLA Polymers Pty Ltd** ACN 004 709 915

Head Office  
215 Colchester Road  
Kilsyth, Victoria, 3137  
Tel: 1800 242 931

New South Wales  
5A 246 Miller Road  
Villawood, NSW, 2163

Queensland  
57 Fulcrum Street  
Richlands, QLD, 4077

South Australia  
Unit 2/7 Berger Road  
Wingfield, SA, 5013

Western Australia  
24 Hanwell Way  
Bassendean, W.A, 6054  
Tel: 08 9279 8911

For the latest product information please visit [rlapolymers.com.au](http://rlapolymers.com.au)