

# ENDCHECK

## TIMBER “CHECK” PREVENTION SOLUTION



### **DESCRIPTION:**

**RLA ENDCHECK** is designed for the control of moisture in timber to prevent splitting. Suitable for application to drying timber to reduce the incidence of checks during the drying process.

### **FEATURES & BENEFITS**

- Easy and ready to use
- Can be diluted with water
- Applied by brush roller or spray
- Can be pigmented to identify application areas

### **APPLICATION:**

- Apply directly to timber surface by brush, roller or knapsack spray
- Apply to freshly sawn logs or timber before air drying or kiln drying

### **COVERAGE**

Apply at a rate of 4 – 6m<sup>2</sup> per litre

### **CLEAN UP**

Clean up equipment with water

### **SHELF LIFE/STORAGE**

- Store in a cool, dry place out of direct sunlight and off of cold floors
- Shelf life is 12 months from date of manufacture when stored as per the above conditions

### **CONTAINER SIZES**

- 20Litre pails
- 200Litre drums

### **LIMITATIONS**

Timber coated with Endcheck may not be suitable for the application of paints or coatings. It is recommended that adhesion of any paints or coatings to be used over timber treated with RLA ENDCHECK is tested over a typical area of the prepared surface to ensure satisfactory adhesion

### **HEALTH AND SAFETY**

For information and advice on the safe handling, first aid, storage and disposal of chemical products, users must refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

### **PRODUCT INFORMATION:**

<b>Appearance</b>	Wet: Milky white liquid Dry: Clear
<b>Solids content</b>	46%
<b>Specific Gravity</b>	0.96 @ 15°C

**WARRANTY STATEMENT:**

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that this product is suitable for use when fully cured and will perform as described in our technical data sheet or other published materials.

RLA Polymers will replace the product free of charge when purchased from any legally verifiable source and where a product is proven to have been stored, handled, and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out in accordance with relevant Australian Standards.

Warranty doesn't apply if damage, loss, failure to follow instructions, or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to RLA Polymers.

The consumer is responsible for any expenses incurred in making a claim.

A claim form can be requested by:

**PHONE:** 1800 242 931

**EMAIL:** [info@rlapolymers.com.au](mailto:info@rlapolymers.com.au)

**MAIL:** 215 Colchester Road Kilsyth Victoria 3137  
(Attention Customer Service)

**WEBSITE:** [www.rlapolymers.com.au](http://www.rlapolymers.com.au)

**AUSTRALIAN CONSUMER LAW:**

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality, and the failure does not amount to a major failure. The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

**DISCLAIMER:**

All statements and technical information contained herein are based on tests we believe to be reliable, but the accuracy thereof is not guaranteed.

Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.