

205 BRUSH CONTACT ADHESIVE HEAT RESISTANT GRADE



DESCRIPTION:

205 BRUSH CONTACT ADHESIVE HEAT RESISTANT GRADE is a HIGH QUALITY contact adhesive with a good brushing consistency. The adhesive is HEAT RESISTANT, has a LONG OPEN TIME and bonds a wide range of materials including decorative plastic laminates, MDF and particleboard, timber, metal, concrete, rubber, glass fabric and urethane foam.

USES:

- Decorative laminates for cabinet making and shopfitting applications
- Auto upholstery

SURFACE PREPARATION

Surfaces to be bonded should be clean and free from oil, dust, loose and other foreign materials. Metal surfaces should be degreased with TAC 101 CONTACT CLEANER

APPLICATION:

- Coverage rate, evaporation time, open time and press time are dependent on type of materials to be bonded as well as workshop conditions such as temperature and humidity
- Do not use below 10°C as condensed water may form on the adhesive film and prevent bonding.
- Best results are obtained under the following conditions:
 - Workshop, material and glue temperature: 20°C
 - Wood moisture: 8 - 10%
 - Relative humidity: 60 - 70%
- Apply adhesive evenly to both surfaces with brush, roller or scraper
- Allow adhesive to evaporate until it is no longer tacky to touch
- Join surfaces before end of open time
- Apply as much pressure as possible to obtain optimum bond strength

COVERAGE

4m²/Litre

DRYING TIMES:

- Evaporation Time @ 20°C: 5 - 10 minutes
- Open Time @ 20°C: 10 - 15 minutes

CLEAN UP:

Use TAC 101 CONTACT CLEANER

SHELF LIFE/STORAGE

- Store under cover, out of direct sunlight and in a well ventilated area.
- Keep away from all sources of ignition
- Shelf life is 12 months when stored as per above recommendations

CONTAINER SIZES

4L, 20L and 200L containers

HEALTH AND SAFETY

For information and advice on the safe handling, first aid, storage and disposal of chemical products, users must refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

TECHNICAL DATA:

Base	Polychloroprene
Colour	Clear (yellow)
Viscosity	Brushable Liquid

WARRANTY STATEMENT:

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that this product is suitable for use when fully cured and will perform as described in our technical data sheet or other published materials.

RLA Polymers will replace the product free of charge when purchased from any legally verifiable source and where a product is proven to have been stored, handled, and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out in accordance with relevant Australian Standards.

Warranty doesn't apply if damage, loss, failure to follow instructions, or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to RLA Polymers.

The consumer is responsible for any expenses incurred in making a claim.

A claim form can be requested by:

PHONE: 1800 242 931

EMAIL: info@rlapolymers.com.au

MAIL: 215 Colchester Road Kilsyth Victoria 3137
(Attention Customer Service)

WEBSITE: www.rlapolymers.com.au

AUSTRALIAN CONSUMER LAW:

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality, and the failure does not amount to a major failure. The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

DISCLAIMER:

All statements and technical information contained herein are based on tests we believe to be reliable, but the accuracy thereof is not guaranteed.

Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.