

RLA UniPrime

Acrylic Based Primer



DESCRIPTION:

RLA Uniprime is an acrylic-based universal wall/floor primer used before applying RLA Tile Adhesives.

RECOMMENDED USE:

- RLA Uniprime increases the adhesion of RLA Tile Adhesives onto the substrate.
- RLA Uniprime must be applied onto timber floors before using RLA Tile Adhesives.
- RLA Uniprime can be applied to concrete, timber, and common building substrates.
- Apply in temperatures above 5°C and below 40°C

SURFACE PREPARATION:

Ensure all surfaces are sound, dry, and free from excessive movement, oil, dust, grease, wax, curing compounds. release agents, paint, and other loose contaminating materials.

Porous Substrates apply **NEAT**.

Non-Porous surfaces like existing tiles, sheet vinyl etc. or contaminated surfaces, use <u>RLA UNIVERSAL PRIMER</u> or consult your local RLA Office

APPLICATION:

When applying the primer onto floor surfaces, it is recommended to pour some primer in a section, then spread the primer using a broom, brush or roller. Then continue this method of application until the entire area is primed.

Note: This application method ensures a thorough coat of the primer on the surface.

Allow the primer to dry for approximately 10 minutes at 20°C before commencing tiling/waterproofing.

No mixing is required, apply RLA Uniprime **NEAT** to substrates.

SETTING TIMES:

Allow the primer to dry for approximately 30 minutes @ 20°C before applying subsequent products. Drying time may vary depending on substrate absorbency and climate conditions.

CLEAN UP:

Excess primer, tools and other equipment can be cleaned up using water while the primer is still wet.

SHELF LIFE / STORAGE:

12 months when stored in original unopened packaging To be stored in a dry area off the ground.

CONTAINER SIZES:

1litre, 5 litre & 20 litre containers

COVERAGE:

Approximately 8m² to 10m² per litre. Spread rates may vary depending on substrate absorbency.

SAFETY & HANDLING:

- Wear suitable respiratory protection.
- Use in well-ventilated areas.
- Avoid breathing vapours
- Avoid contact with skin and eyes.
- Wear eye protection and suitable gloves and clothing.
- Do not eat, drink, or smoke while using this product.
- If on the skin, wash with plenty of soap and water.
- If in the eves: rinse cautiously with water for several minutes.
- Remove contact lenses; if present, continue rinsing.
- If any skin or eye irritation persists or you feel unwell, get medical attention.

Safety Data Sheet is available upon request.

FIRST AID:

If poisoning occurs, contact a doctor or Poisons Information Centre.

Skin: Wash off with warm water and soap.

If swallowed, DO NOT induce vomiting. Give a glass of

For advice or you feel unwell contact a Poisons Information Centre: Australia ph 131126,

New Zealand ph 0800 764 766 or a doctor at once.

If swallowed, do NOT induce vomiting.

IF SWALLOWED, immediately call the Poisons Information Centre or a doctor.

IF ON SKIN Remove immediately all contaminated clothing and wash skin with soap and water.

If skin irritation occurs, get medical advice/attention.

IF IN EYES Rinse carefully with water for several minutes. If eye irritation persists, get medical advice/attention.

RLA Polymers Pty Ltd ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria, 3137 info@rlapolymers.com.au

T. 1800 242 931



rlapolymers.com.au





WARRANTY STATEMENT:

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that this product is suitable for use when fully cured and will perform as described in our technical data sheet or other published materials.

RLA Polymers will replace the product free of charge when purchased from any legally verifiable source and where a product is proven to have been stored, handled, and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out per the relevant Australian Standard, the Floorcovering Manufacturer's instructions, and the floorcoverings must have been subject to normal traffic conditions.

Warranty doesn't apply if damage, loss, failure to follow instructions, or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to RLA Polymers.

The consumer is responsible for any expenses incurred in making a claim.

A claim form can be requested by:

PHONE: 1800 242 931

EMAIL: info@rlapolymers.com.au

MAIL: 215 Colchester Road Kilsvth Victoria 3137 (Attention Customer Service)

WEBSITE: www.rlapolymers.com.au

AUSTRALIAN CONSUMER LAW:

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality, and the failure does not amount to a major failure. The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

DISCLAIMER:

All statements and technical information contained herein are based on tests we believe to be reliable, but the accuracy thereof is not guaranteed.

Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.

RLA Polymers Pty Ltd ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria, 3137 info@rlapolymers.com.au T. 1800 242 931

